



EMC TEST REPORT

For

Shenzhen Huafurui Technology Co., Ltd.

Smartphone

Test Model: NOTE 50

Prepared for : Shenzhen Huafurui Technology Co., Ltd.
Address : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 15, 2023
Number of tested samples : 2
Serial number : Prototype
Date of Test : May 15, 2023 ~ June 05, 2023
Date of Report : June 07, 2023



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: + (86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| | |
|---|--|
| EMC TEST REPORT | |
| ETSI EN 301 489-1 V2.2.3 (2019-11) & ETSI EN 301 489-3 V2.3.2 (2023-01) & Draft ETSI EN 301 489-17 V3.2.5 (2022-08) & ETSI EN 301 489-19 V2.2.1 (2022-09) & ETSI EN 301 489-52 V1.2.1 (2021-11) | |
| Report Reference No. | LCSA051523066EA |
| Date Of Issue | June 07, 2023 |
| Testing Laboratory Name | Shenzhen LCS Compliance Testing Laboratory Ltd. |
| Address | Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China |
| Testing Location/ Procedure | Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/> |
| Applicant's Name | Shenzhen Huafurui Technology Co., Ltd. |
| Address | Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China |
| Test Specification | |
| Standard | ETSI EN 301 489-1 V2.2.3 (2019-11) ETSI EN 301 489-3 V2.3.2 (2023-01) Draft ETSI EN 301 489-17 V3.2.5 (2022-08) ETSI EN 301 489-19 V2.2.1 (2022-09) ETSI EN 301 489-52 V1.2.1 (2021-11) |
| Test Report Form No. | LCSEMC-1.0 |
| TRF Originator | Shenzhen LCS Compliance Testing Laboratory Ltd. |
| Master TRF | Dated 2017-06 |
| Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. | |
| Test Item Description | |
| Trade Mark | CUBOT |
| Test Model | NOTE 50 |
| Ratings | Input: 5.0V=2.0A For AC Adapter Input: 100-240V~, 50/60Hz, 0.3A Adapter Output: 5.0V=2.0A, 10.0W DC 3.87V by Rechargeable Li-ion Battery, 5200mAh |
| Result | Positive |

Compiled by:

Kevin Huang

Supervised by:

Cary Luo

Approved by:

Gavin Liang

Kevin Huang/ Administrator

Cary Luo/ Technique principal

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



EMC -- TEST REPORT

Test Report No. : LCSA051523066EAJune 07, 2023

Date of issue

Test Model..... : NOTE 50

EUT..... : Smartphone

Applicant..... : Shenzhen Huafurui Technology Co., Ltd.

Address..... : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Telephone..... : /

Fax..... : /

Manufacturer..... : Shenzhen Huafurui Technology Co., Ltd.

Address..... : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Telephone..... : /

Fax..... : /

Factory..... : Shenzhen Huafurui Technology Co., Ltd.

Address..... : Unit 1401 & 1402, 14/F, Jinqi Zhigu Mansion (No. 4 Building of Chongwen Garden), Crossing of the Liuxian Street and Tangling Road, Taoyuan Street, Nanshan District, Shenzhen, 518055, P.R. China

Telephone..... : /

Fax..... : /

Test Result**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Revision History

| Report Version | Issue Date | Revision Content | Revised By |
|----------------|---------------|------------------|------------|
| 000 | June 07, 2023 | Initial Issue | --- |
| | | | |
| | | | |





TABLE OF CONTENTS

| | |
|--|-----------|
| 1. GENERAL INFORMATION | 6 |
| 1.1. PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 6 |
| 1.2. OBJECTIVE | 9 |
| 1.3. RELATED SUBMITTAL(S)/GRANT(S) | 9 |
| 1.4. TEST METHODOLOGY | 9 |
| 1.5. DESCRIPTION OF TEST FACILITY | 9 |
| 1.6. SUPPORT EQUIPMENT LIST | 10 |
| 1.7. EXTERNAL I/O | 10 |
| 1.8. MEASUREMENT UNCERTAINTY | 10 |
| 1.9. DESCRIPTION OF TEST MODES | 11 |
| 2. SUMMARY OF TEST RESULTS | 12 |
| 3. TEST RESULTS | 13 |
| 3.1. LINE CONDUCTED EMISSION | 13 |
| 3.2. CONDUCTED EMISSION (WIRED NETWORK PORT) | 15 |
| 3.3. RADIATED DISTURBANCE | 16 |
| 3.4. HARMONIC CURRENT EMISSIONS | 19 |
| 3.5. VOLTAGE FLUCTUATION AND FLICKER | 20 |
| 3.6. RF ELECTROMAGNETIC FIELD (80 MHZ - 6000 MHZ) | 21 |
| 3.7. ELECTROSTATIC DISCHARGE | 23 |
| 3.8. ELECTRICAL FAST TRANSIENT IMMUNITY | 25 |
| 3.9. RF COMMON MODE | 26 |
| 3.10. SURGES, LINE TO LINE AND LINE TO GROUND | 28 |
| 3.11. VOLTAGE DIPS/INTERRUPTIONS IMMUNITY TEST | 29 |
| 4. GENERAL PERFORMANCE CRITERIA FOR IMMUNITY TEST | 30 |
| 4.1. PERFORMANCE CRITERIA FOR CONTINUOUS PHENOMENA APPLIED TO TRANSMITTER (CT) | 30 |
| 4.2. PERFORMANCE CRITERIA FOR TRANSIENT PHENOMENA APPLIED TO TRANSMITTER (TT) | 30 |
| 4.3. PERFORMANCE CRITERIA FOR CONTINUOUS PHENOMENA APPLIED TO RECEIVER (CR) | 30 |
| 4.4. PERFORMANCE CRITERIA FOR TRANSIENT PHENOMENA APPLIED TO RECEIVER (TR) | 30 |
| 5. LIST OF MEASURING EQUIPMENT | 33 |
| 6. PHOTOGRAPHS OF TEST SETUP | 35 |
| 7. PHOTOGRAPHS OF THE EUT | 35 |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT : Smartphone

Test Model : NOTE 50

Power Supply : Input: 5.0V \pm 2.0A
For AC Adapter Input: 100-240V~, 50/60Hz, 0.3A
Adapter Output: 5.0V \pm 2.0A, 10.0W
DC 3.87V by Rechargeable Li-ion Battery, 5200mAh

Hardware Version : G2233G-UF-V1.1

Software Version : CUBOT_NOTE_50_D041C_V1.0

Bluetooth :

Frequency Range : 2402MHz~2480MHz

Channel Number : 79 channels for Bluetooth V5.0 (BDR/EDR)
40 channels for Bluetooth V5.0 (BT LE)

Channel Spacing : 1MHz for Bluetooth V5.0 (BDR/EDR)
2MHz for Bluetooth V5.0 (BT LE)

Modulation Type : GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (BDR/EDR)
GFSK for Bluetooth V5.0 (BT LE)

Bluetooth Version : V5.0

Antenna Description : PIFA Antenna, 2.63dBi(Max.)

WIFI(2.4G Band) :

Frequency Range : 2412MHz~2472MHz

Channel Spacing : 5MHz

Channel Number : 13 Channel for 20MHz bandwidth(2412~2472MHz)

Modulation Type : 802.11b: DSSS (CCK, DQPSK, DBPSK)
802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)

Antenna Description : PIFA Antenna, 2.63dBi(Max.)

WIFI(5.2G Band) :

Frequency Range : 5180MHz~5240MHz

Channel Number : 4 channels for 20MHz bandwidth(5180~5240MHz)
2 channels for 40MHz bandwidth(5190~5230MHz)
1 channels for 80MHz bandwidth(5210MHz)

Modulation Type : 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : PIFA Antenna, 1.74dBi(Max.)

WIFI(5.8G Band) :

Frequency Range : 5745MHz~5825MHz

Channel Number : 5 channels for 20MHz bandwidth(5745~5825MHz)
2 channels for 40MHz bandwidth(5755~5795MHz)
1 channels for 80MHz bandwidth(5775MHz)

Modulation Type : 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : PIFA Antenna, 1.74dBi(Max.)

2G :

Support Band : ☒ GSM 900 (EU-Band)
☒ DCS 1800 (EU-Band)

Release Version : R99

GPRS Class : Class 12

EGPRS Class : Class 12

Uplink : GSM 900: 880MHz~915MHz
DCS 1800: 1710MHz~1785MHzDownlink : GSM 900: 925MHz~960MHz
DCS 1800: 1805MHz~1880MHz

Type Of Modulation : GMSK for GSM/GPRS; GMSK/8PSK for EGPRS

Antenna Description : PIFA Antenna

-3.38dBi (max.) For GSM 900

-0.49dBi (max.) For DCS 1800

Power Class : GSM 900: Level 5, DCS 1800: Level 0
EGPRS 900: Level 8, EGPRS 1800: Level 2

3G :

Support Band : ☒ WCDMA Band I (EU-Band)
☒ WCDMA Band VIII (EU-Band)

Release Version : R8

Uplink : WCDMA Band I: 1920MHz~1980MHz
WCDMA Band VIII: 880MHz~915MHzDownlink : WCDMA Band I: 2110MHz~2170MHz
WCDMA Band VIII: 925MHz~960MHz

Type Of Modulation : QPSK/16QAM

Antenna Description : PIFA Antenna

-3.71dBi (max.) For WCDMA Band I

-3.38dBi (max.) For WCDMA Band VIII

Power Class : Level 3

LTE :

Support Band : ☒ E-UTRA Band 1(EU-Band)
☒ E-UTRA Band 3(EU-Band)
☒ E-UTRA Band 7(EU-Band)
☒ E-UTRA Band 8(EU-Band)
☒ E-UTRA Band 20(EU-Band)
☒ E-UTRA Band 38(EU-Band)
☒ E-UTRA Band 40(EU-Band)

LTE Release Version : R9

FDD Band : Uplink: E-UTRA Band 1: 1920MHz~1980MHz
E-UTRA Band 3: 1710MHz~1785MHz
E-UTRA Band 7: 2500MHz~2570MHz
E-UTRA Band 8: 880MHz~915MHz

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity





E-UTRA Band 20: 832MHz~862MHz
Downlink: E-UTRA Band 1: 2110MHz~2170MHz
E-UTRA Band 3: 1805MHz~1880MHz
E-UTRA Band 7: 2620MHz~2690MHz
E-UTRA Band 8: 925MHz~960MHz
E-UTRA Band 20: 791MHz~821MHz
TDD Band : E-UTRA Band 38: 2570MHz~2620MHz
E-UTRA Band 40: 2300MHz~2400MHz
Type Of Modulation : QPSK/16QAM
Antenna Description : PIFA Antenna
-3.71dBi (max.) For E-UTRA Band 1
-1.05dBi (max.) For E-UTRA Band 3
-0.80dBi (max.) For E-UTRA Band 7
-3.38dBi (max.) For E-UTRA Band 8
-1.60dBi (max.) For E-UTRA Band 20
-0.80dBi (max.) For E-UTRA Band 38
1.65dBi (max.) For E-UTRA Band 40
Power Class : Class 3
GPS Receiver :
Receive Frequency : 1575.42MHz
Channel Number : 1
Antenna Description : PIFA Antenna, 0.77dBi(Max.)
BDS Receiver :
Receive Frequency : 1561.098MHz
Channel Number : 1
Antenna Description : PIFA Antenna, 0.77dBi(Max.)
NFC :
Frequency Range : 13.56MHz
Modulation Type : ASK
Antenna Description : PIFA Antenna, 0dBi(Max.)





1.2. Objective

| | |
|--------------------|--|
| ETSI EN 301 489-1 | ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard for ElectroMagnetic Compatibility |
| ETSI EN 301 489-3 | ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 3: Specific conditions for Short Range Devices (SRD) operating on frequencies between 9 kHz and 246 GHz; Harmonised Standard for ElectroMagnetic Compatibility |
| ETSI EN 301 489-17 | ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for Broadband and Wideband Data Transmission Systems; Harmonised Standard for ElectroMagnetic Compatibility |
| ETSI EN 301 489-19 | ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 19: Specific conditions for Receive Only Mobile Earth Stations (ROMES) operating in the 1,5 GHz band providing data communications and GNSS receivers operating in the RNSS band providing positioning, navigation, and timing data; Harmonised Standard for ElectroMagnetic Compatibility |
| ETSI EN 301 489-52 | ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 52: Specific conditions for Cellular Communication User Equipment (UE) radio and ancillary equipment; Harmonised Standard for ElectroMagnetic Compatibility |

The objective is to determine compliance with ETSI EN 301 489-1 V2.2.3 (2019-11), ETSI EN 301 489-3 V2.3.2 (2023-01), Draft ETSI EN 301 489-17 V3.2.5 (2022-08), ETSI EN 301 489-19 V2.2.1 (2022-09), ETSI EN 301 489-52 V1.2.1 (2021-11).

1.3. Related Submittal(s)/Grant(s)

No Related Submittals.

1.4. Test Methodology

All measurements contained in this report were conducted with ETSI EN 301 489-1 V2.2.3 (2019-11), ETSI EN 301 489-3 V2.3.2 (2023-01), Draft ETSI EN 301 489-17 V3.2.5 (2022-08), ETSI EN 301 489-19 V2.2.1 (2022-09), ETSI EN 301 489-52 V1.2.1 (2021-11).

1.5. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



1.6. Support Equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------------------------------|------------------|-----------------|---------------|-------------|
| ShenZhen HuaJin Electronics CO., LTD | AC Power Adapter | HJ-0502000W2-EU | --- | CE |

1.7. External I/O

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-----------------------------|
| Type-C USB Port | 1 | USB Cable: 1.0m, unshielded |

1.8. Measurement Uncertainty

| Item | MU | Remark |
|---|---------|-------------|
| Uncertainty for Power point Conducted Emissions Test | 2.42dB | |
| Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz) | 3.54dB | Polarize: V |
| | 4.1dB | Polarize: H |
| Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz) | 2.08dB | Polarize: H |
| | 2.56dB | Polarize: V |
| Uncertainty for radio frequency | 0.01ppm | |
| Uncertainty for conducted RF Power | 0.65dB | |
| Uncertainty for temperature | 0.2℃ | |
| Uncertainty for humidity | 1% | |
| Uncertainty for DC and low frequency voltages | 0.06% | |





1.9. Description of Test Modes

There was 33 test Modes. TM1 to TM33 were shown below:

| | | |
|------|---|--|
| TM1 | : | Operate in traffic mode GSM 900; |
| TM2 | : | Operate in traffic mode GPRS 900; |
| TM3 | : | Operate in traffic mode EGPRS 900; |
| TM4 | : | Operate in traffic mode DCS 1800; |
| TM5 | : | Operate in traffic mode GPRS 1800; |
| TM6 | : | Operate in traffic mode EGPRS 1800; |
| TM7 | : | Operate in traffic mode WCDMA For band I; |
| TM8 | : | Operate in traffic mode HSUPA For band I; |
| TM9 | : | Operate in traffic mode HSDPA For band I; |
| TM10 | : | Operate in traffic mode WCDMA For band VIII; |
| TM11 | : | Operate in traffic mode HSUPA For band VIII; |
| TM12 | : | Operate in traffic mode HSDPA For band VIII; |
| TM13 | : | Operate in traffic mode For E-UTRA Band 1; |
| TM14 | : | Operate in traffic mode For E-UTRA Band 3; |
| TM15 | : | Operate in traffic mode For E-UTRA Band 7; |
| TM16 | : | Operate in traffic mode For E-UTRA Band 8; |
| TM17 | : | Operate in traffic mode For E-UTRA Band 20; |
| TM18 | : | Operate in traffic mode For E-UTRA Band 38; |
| TM19 | : | Operate in traffic mode For E-UTRA Band 40; |
| TM20 | : | Operate in Bluetooth mode; |
| TM21 | : | Operate in 2.4G WIFI mode; |
| TM22 | : | Operate in 5.2G WIFI mode; |
| TM23 | : | Operate in 5.8G WIFI mode; |
| TM24 | : | Operate in GPS (RX) mode; |
| TM25 | : | Operate in BDS (RX) mode; |
| TM26 | : | Operate in NFC mode; |
| TM27 | : | Playing Music mode; |
| TM28 | : | Video playing mode; |
| TM29 | : | Camera mode; |
| TM30 | : | Exchange Data With PC; |
| TM31 | : | Operate in charging mode; |
| TM32 | : | Idle mode; |

***Note:

1. The EUT has two SIM card slots(SIM1 and SIM2). The result for GSM/WCDMA/LTE card slot(SIM1) is the worst case which was only recorded.
2. All test modes were tested, but we only recorded the worst case in this report.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



2. SUMMARY OF TEST RESULTS

| Rule | Description of Test Items | Result |
|------|---|-----------|
| §7.1 | Reference to clause 8.4 of ETSI EN 301 489-1 Conducted Emission (AC mains input/output port) | Compliant |
| §7.1 | Reference to clause 8.3 of ETSI EN 301 489-1 Conducted Emission (DC power input/output port) | N/A* |
| §7.1 | Reference to clause 8.7 of ETSI EN 301 489-1 Conducted Emission (Wired network port) | N/A* |
| §7.1 | Reference to clause 8.2 of ETSI EN 301 489-1 Radiated Emission (Enclosure of ancillary equipment) | Compliant |
| §7.1 | Reference to clause 8.5 of ETSI EN 301 489-1 Harmonic current emissions (AC mains input port) | N/A* |
| §7.1 | Reference to clause 8.6 of ETSI EN 301 489-1 Voltage fluctuations and flicker (AC mains input port) | Compliant |
| §7.2 | Reference to clause 9.3 of ETSI EN 301 489-1 Electrostatic discharge (Enclosure port) (EN 61000-4-2) | Compliant |
| §7.2 | Reference to clause 9.2 of ETSI EN 301 489-1 RF electromagnetic field (80MHz to 6000MHz) (Enclosure port) (EN 61000-4-3) | Compliant |
| §7.2 | Reference to clause 9.4 of ETSI EN 301 489-1 Fast transients common mode (signal, wired network and control ports, DC and AC power ports) (EN 61000-4-4) | Compliant |
| §7.2 | Reference to clause 9.8 of ETSI EN 301 489-1 Surges, line to line and line to ground (AC mains power input ports, wired network ports) (EN 61000-4-5) | Compliant |
| §7.2 | Reference to clause 9.5 of ETSI EN 301 489-1 RF common mode 0.15MHz to 80MHz (signal, wired network and control ports, DC and AC power ports) (EN 61000-4-6) | Compliant |
| §7.2 | Reference to clause 9.6 of ETSI EN 301 489-1 Transients and surges in the vehicular environment (ISO 7637-2) | N/A* |
| §7.2 | Reference to clause 9.7 of ETSI EN 301 489-1 Voltage dips and interruptions (AC mains power input ports) (EN 61000-4-11) | Compliant |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street,
Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3. TEST RESULTS

3.1. Line Conducted Emission


3.1.1 Conducted Emission Limit

Relevant Standard(s): ETSI EN 301 489-1 V2.2.3 (2019-11) / EN 55032:2015/A11:2020
Class B

| Limits for Line Conducted Emission | | |
|------------------------------------|--------------------|---------------|
| Frequency (MHz) | Limit (dB μ V) | |
| | Quasi-peak Level | Average Level |
| 0.15 ~ 0.50 | 66.0 ~ 56.0 * | 56.0 ~ 46.0 * |
| 0.50 ~ 5.00 | 56.0 | 46.0 |
| 5.00 ~ 30.00 | 60.0 | 50.0 |

NOTE1-The lower limit shall apply at the transition frequencies.
NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

3.1.2 Test Configuration



The setup of EUT is according with per ETSI EN 301 489-1 measurement procedure. The specification used was with the ETSI EN 301 489-1 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The EUT received charging power from the charger which received power through a LISN supplying power of AC 230V/50Hz.





3.1.3 EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Receiver Parameter | Setting |
|------------------------|----------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 150KHz ~ 30MHz |
| (IF)RBW | 9kHz |

All data was recorded in the Quasi-peak and average detection mode.

3.1.4 Test Procedure

Power on the EUT, the EUT begins to work. Make sure the EUT operates normally during the test.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

3.1.5 Test Results

PASS

Please refer to Appendix A.1 for Emission and Immunity test results.





3.2. Conducted Emission (Wired Network Port)


3.2.1 Conducted Emission Limit(Wired Network Port)

| Limits for asymmetric mode conducted emissions | | | | |
|--|--|------------------|--|------------------|
| Frequency (MHz) | Class B voltage limits (dB μ V) | | Class B current limits (dB μ A) | |
| | Quasi-peak Level | Average Level | Quasi-peak Level | Average Level |
| 0.15 ~ 0.50 | 84.0~74.0 | 74.0~64.0 | 40.0~30.0 | 30.0~20.0 |
| 0.50 ~ 30.00 | 74.0 | 64.0 | 30.0 | 20.0 |

NOTE 1-The limits decrease linearly with the logarithm of the frequency in the range 0,15 MHz to 0,5 MHz.

NOTE 2-The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150 / I = 44$ dB).

3.2.2 Test Configuration



3.2.3 EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Receiver Parameter | Setting |
|------------------------|----------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 150KHz ~ 30MHz |
| (IF)RBW | 9kHz |

All data was recorded in the Quasi-peak and average detection mode.

3.2.4 Test Procedure

Please refer to ETSI EN 301 489-1 Clause 8.7.2 and EN 55032 Clause 6 for the measurement methods.

3.2.5 Test Results

Not applicable.





3.3. Radiated Disturbance

3.3.1 Radiated Emission Limit

Relevant Standard(s): ETSI EN 301 489-1 V2.2.3 (2019-11) / EN 55032:2015/A11:2020
Class B

| Limits for Radiated Disturbance Below 1GHz | | | |
|--|-------------------|---------------------------|--------------------------------------|
| Frequency (MHz) | Facility | Distance (Meters) | Field Strengths Limit (dB μ V/m) |
| 30 ~ 230 | FAR | 3 | 42-35 |
| 230 ~ 1000 | FAR | 3 | 42 |
| ***Note: (1) The smaller limit shall apply at the combination point between two frequency bands. (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT. | | | |
| Limits for Radiated Disturbance Above 1GHz | | | |
| Frequency (MHz) | Distance (Meters) | Peak Limit (dB μ V/m) | Average Limit (dB μ V/m) |
| 1000 ~ 3000 | 3 | 70 | 50 |
| 3000 ~ 6000 | 3 | 74 | 54 |
| ***Note: The lower limit applies at the transition frequency. | | | |

| Limits for Radiated Disturbance Below 1GHz (For FM Receivers) | | | |
|---|-------------------|------------------------|-----------|
| Frequency (MHz) | Distance (Meters) | Class B Limit (dBμV/m) | |
| | | Fundamental | Harmonics |
| 30 ~ 230 | 3 | 60 | 52 |
| 230 ~ 300 | 3 | | 52 |
| 300 ~ 1000 | 3 | | 56 |
| ***Note: These relaxed limits apply only to emissions at the fundamental and harmonic frequencies of the LO. Signals at all other frequencies shall be compliant with the limits given in above Table. | | | |
| | | | |
| Limits for Radiated Disturbance Above 1GHz (For FM Receivers) | | | |
| 1000 ~ 3000 | 3 | 70 | 50 |
| 3000 ~ 6000 | 3 | 74 | 54 |
| ***Note: The lower limit applies at the transition frequency. | | | |





3.3.2 Test Configuration




Figure C.1 – Measurement distance

Test Setup for FM Receiver






Figure C.2 – Boundary of EUT, Local AE and associated cabling

Test Setup for FM Receiver

3.3.3 Test Procedure

The test method shall be in accordance with CENELEC EN 55032 [1], annex A.3.

3.3.4 Test Results

PASS


Please refer to Appendix A.3 for Emission and Immunity test results.





3.4. Harmonic Current Emissions

3.4.1 Test Configuration



3.4.2 Test Standard

According to ETSI EN 301 489-1 V2.2.3 (2019-11) & EN 61000-3-2: 2014

3.4.3 Test Results

N/A


Please refer to Appendix A.4 for Emission and Immunity test results.





3.5. Voltage Fluctuation and Flicker

3.5.1 Test Configuration



3.5.2 Test Standard

According to ETSI EN 301 489-1 V2.2.3 (2019-11) & EN 61000-3-3: 2013

3.5.3 Test Results

PASS


Please refer to Appendix A.5 for Emission and Immunity test results.





3.6. RF Electromagnetic Field (80 MHz - 6000 MHz)

3.6.1 Test Configuration



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.6.2 Test Standard

ETSI EN 301 489-1, ETSI EN 301 489-3, ETSI EN 301 489-17, ETSI EN 301 489-19, ETSI EN 301 489-52 (EN 61000-4-3: 2006+A2: 2010)

Test level 2 at 3V/m.

3.6.3 Severity Level

| Level | Field Strength (V/m) |
|---------------------------------|----------------------|
| 1 | 1 |
| 2 | 3 |
| 3 | 10 |
| X | Special |
| Performance Criterion: A | |

3.6.4 Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. EUT is set 3 meter away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna are set on test. Each of the four sides of EUT must be faced this transmitting antenna and measured individually. In order to judge the EUT performance, a CCD camera is used to monitor EUT screen. All the scanning conditions are as follows:

| Condition of Test | Remark |
|------------------------|--------------------------|
| Fielded Strength | 3 V/m (Severity Level 2) |
| Radiated Signal | Unmodulated |
| Scanning Frequency | 80-6000MHz |
| Dwell time of radiated | 0.0015 decade/s |
| Waiting Time | 3 Sec. |

3.6.5 Test Results


PASS

Please refer to Appendix A.6 for Emission and Immunity test results.



3.7. Electrostatic Discharge

3.7.1 Test Configuration



EN 61000-4-2 specifies that a tabletop EUT shall be placed on a non-conducting table which is 80 centimeters above a ground reference plane and that floor mounted equipment shall be placed on a insulating support approximately 10 centimeters above a ground plane. During the tests, the EUT is positioned over a ground reference plane in conformance with this requirement.

For tabletop equipment, a 1.5 by 1.0-meter metal sheet (HCP) is placed on the table and connected to the ground plane via a metal strap with two 470 k Ohms resistors in series. The EUT and attached cables are isolated from this metal sheet by 0.5-millimeter thick insulating material. A Vertical Coupling Plane (VCP) grounded on the ground plane through the same configuration as in the HCP is used.

3.7.2 Test Procedure

ETSI EN 301 489-1 V2.2.3 (2019-11) / EN 61000-4-2: 2009

Test level 3 for Air Discharge at ± 8 kV

Test level 2 for Contact Discharge at ± 4 kV

3.7.2.1 Air Discharge

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

3.7.2.2 Contact Discharge

All the procedure shall be same as Section 3.7.2.1. except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

3.7.2.3 Indirect Discharge For Horizontal Coupling Plane

At least 10 single discharges (in the most sensitive polarity) shall be applied at the front edge of each HCP opposite the center point of each unit (if applicable) of the EUT and 0.1m from the front of the EUT. The long axis of the discharge electrode shall be in the plane of the HCP and perpendicular to its front edge during the discharge.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.7.2.4 Indirect Discharge For Vertical Coupling Plane

At least 10 single discharges (in the most sensitive polarity) shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

3.7.3 Test Results

PASS

Please refer to Appendix A.7 for Emission and Immunity test results.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.8. Electrical Fast Transient Immunity

3.8.1 Test Configuration



3.8.2 Test Standard

ETSI EN 301 489-1 V2.2.3 (2019-11)/ EN61000-4-4: 2012

Test level 2 at 1 kV

| Test Level | | |
|---|-----------------------|---|
| Open Circuit Output Test Voltage $\pm 10\%$ | | |
| Level | On Power Supply Lines | On I/O (Input/Output) Signal data and control lines |
| 1 | 0.5 kV | 0.25 kV |
| 2 | 1 kV | 0.5 kV |
| 3 | 2 kV | 1 kV |
| 4 | 4 kV | 2 kV |
| X | Special | Special |
| Performance Criterion: B | | |

3.8.3 Test Procedure

The EUT is put on the table, which is 0.8 meter high above the ground. This reference ground plane shall project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5m.

3.8.3.1 For input and output AC power ports:

The EUT is connected to the power mains by using a coupling device, which couples the EFT interference signal to AC power lines. Both polarities of the test voltage should be applied during compliance test and the duration of the test is 2 minutes.

3.8.3.2 For signal lines and control lines ports: No I/O ports. It's unnecessary to test.

3.8.3.3 For DC output line ports: It's unnecessary to test.

3.8.4 Test Results

PASS

Please refer to Appendix A.8 for Emission and Immunity test results.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.9. RF Common Mode

3.9.1 Test Configuration



3.9.2 Test Standard

ETSI EN 301 489-1 V2.2.3 (2019-11)/ EN 61000-4-6: 2014

Test level: 3V (r.m.s.) for 0.15MHz ~ 10MHz; 3V (r.m.s.) to 1V (r.m.s.) for 10MHz ~ 30MHz;

1V (r.m.s.) for 30MHz ~ 80MHz

Modulation type: AM

Modulation depth: 80%

Modulation signal: 1 kHz

| Test Level | |
|------------|----------------------------|
| Level | Voltage Level (r.m.s.) (V) |
| 1 | 1 |
| 2 | 3 |
| 3 | 10 |
| X | Special |

Performance Criterion: A



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.9.3 Test Procedure

3.9.3.1 Let the EUT work in test mode and test it.

3.9.3.2 The EUT are placed on an insulating support 0.1m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane about 0.3m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50mm (where possible).

3.9.3.3 The disturbance signal described below is injected to EUT through CDN.

3.9.3.4 The EUT operates within its operational mode(s) under intended climatic conditions after power on.

3.9.3.5 The frequency range is swept from 150kHz to 10MHz using 3V signal level, 10MHz to 30MHz using 3V to 1V signal level, 30MHz to 80MHz using 1V signal level, and with the disturbance signal 80% amplitude modulated with a 1kHz sine wave.

3.9.3.6 The rate of sweep shall not exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.

3.9.3.7 Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

3.9.4 Test Results

PASS


Please refer to Appendix A.9 for Emission and Immunity test results.





3.10. Surges, Line to Line and Line to Ground

3.10.1 Test Configuration



3.10.2 Test Standard

ETSI EN 301 489-1 V2.2.3 (2019-11) / EN 61000-4-5: 2014+A1:2017

L-N: Test level 2 at 1 kV

L-PE, N-PE Test Level 3 at 2kV

| Test Level | | |
|---|-----------------------|---|
| Open Circuit Output Test Voltage $\pm 10\%$ | | |
| Level | On Power Supply Lines | On I/O (Input/Output) Signal data and control lines |
| 1 | 0.5 kV | 0.25 kV |
| 2 | 1 kV | 0.5 kV |
| 3 | 2 kV | 1 kV |
| 4 | 4 kV | 2 kV |
| X | Special | Special |
| Performance Criterion: B | | |

3.10.3 Test Procedure

3.10.3.1 For line to line coupling mode, provide a 0.5 kV 1.2/50us voltage surge (at open-circuit condition).

3.10.3.2 At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.

3.10.3.3 Different phase angles are done individually.

3.10.3.4 Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

3.10.4 Test Results

PASS

Please refer to Appendix A.10 for Emission and Immunity test results.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.11. Voltage Dips/Interruptions Immunity Test

3.11.1 Test Configuration



3.11.2 Test Standard

ETSI EN 301 489-1 V2.2.3 (2019-11)/ EN 61000-4-11: 2004+A1:2017

Test levels and Performance Criterion

| Test Level | | |
|--------------------------------------|---------------------------------|-------------------------|
| Voltage Reduction %U _T | Voltage Dips %U _T | Duration (in Period) |
| 100 | 0 | 0.5 |
| 100 | 0 | 1 |
| 30 | 70 | 5 |
| Voltage Reduction %U _T | Voltage Dips %U _T | Duration (in Period) |
| 100 | 0 | 250 |
| Performance Criterion: B&C | | |

3.11.3 Test Procedure

3.11.3.1 The interruption is introduced at selected phase angles with specified duration.

3.11.3.2 Record any degradation of performance.

3.11.4 Test Results

PASS

Please refer to Appendix A.11 for Emission and Immunity test results.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4. GENERAL PERFORMANCE CRITERIA FOR IMMUNITY TEST

4.1. Performance criteria for Continuous phenomena applied to Transmitter (CT)

For equipment of type II or type III that requires a communication link that is maintained during the test, it shall be verified by appropriate means supplied by the manufacturer that the communication link is maintained during each individual exposure in the test sequence. Where the EUT is a transmitter, tests shall be repeated with the EUT in standby mode to ensure that any unintentional transmission does not occur.

4.2. Performance criteria for Transient phenomena applied to Transmitter (TT)

For equipment of type II or type III that requires a communication link that is maintained during the test, this shall be verified by appropriate means supplied by the manufacturer during each individual exposure in the test sequence. Where the EUT is a transmitter, tests shall be repeated with the EUT in standby mode to ensure that any unintentional transmission does not occur.

4.3. Performance criteria for Continuous phenomena applied to Receiver (CR)

For equipment of type II or III that requires a communication link that is maintained during the test, it shall be verified by appropriate means supplied by the manufacturer that the communication link is maintained during each individual exposure in the test sequence. Where the EUT is a transceiver, under no circumstances shall the transmitter operate unintentionally during the test.

4.4. Performance criteria for Transient phenomena applied to Receiver (TR)

For equipment of type II or type III that requires a communication link that is maintained during the test, this shall be verified by appropriate means supplied by the manufacturer during each individual exposure in the test sequence. Where the EUT is a transceiver, under no circumstances shall the transmitter operate unintentionally during the test.



**Performance criteria for ETSI EN 301 489-3 V2.3.2 (2023-01)****1) Introduction**

The performance criteria are used to make an assessment whether a radio equipment passes or fails immunity tests.

Only the performance criteria specified in the present document or in ETSI EN 301 489-1 [1] where referenced shall apply.

The provisions of ETSI EN 301 489-1 [1] clause 6 shall apply, together with clauses 6.2 and 6.3 of the present document.

2) Continuous and non-continuous operation

Latency is the time delay between the initiation and the completion of operation of the EUT. Correct functioning requires completing the relevant operation within the maximum latency time.

Where the maximum latency is specified in the applicable harmonised radio standard (in the wanted performance criterion, or an acknowledge requirement), that value shall be used.

Where this is not the case, then the maximum latency is that required by the intended use of the EUT.

3) Operating modes

Where the EUT has more than one mode of operation (see clause 4.4.1), an unplanned transition from one mode to another is considered as an unintentional response. The EUT shall be tested in all modes to confirm there are no such unintentional responses.

Performance criteria for Draft ETSI EN 301 489-17 V3.2.5 (2022-08)

| Criteria | During test | After test (i.e. as a result of the application of the test) |
|----------|--|---|
| A | Shall operate as intended. (See note). Shall be no loss of function. Shall be no unintentional transmissions. | Shall operate as intended. Shall be no degradation of performance. Shall be no loss of function. Shall be no loss of critical stored data. |
| B | May be loss of function. | Functions shall be self-recoverable. Shall operate as intended after recovering. Shall be no loss of critical stored data. |
| C | May be loss of function. | Functions shall be recoverable by the operator. Shall operate as intended after recovering. Shall be no loss of critical stored data. |

NOTE: Operate as intended during the test allows a level of degradation in accordance with clause 6.2.2.





Performance criteria for ETSI EN 301 489-19 V2.2.1 (2022-09)

1) Introduction

Only the performance criteria specified in the present document or in ETSI EN 301 489-1 [1] where referenced shall apply.

The equipment shall meet the minimum performance criteria as specified in clauses 6.1 and 6.2 as appropriate.

For the purpose of the present document two categories of performance criteria apply:

- Performance criteria for continuous phenomena.
- Performance criteria for transient phenomena.

2) Performance criteria for Continuous phenomena

During the test, the equipment shall operate as intended, e.g. not unintentionally change its operating state and not unintentionally change critical stored data. After the test, the equipment shall operate as intended, e.g. have no loss of function and have no loss of critical stored data.

3) Performance criteria for Transient phenomena

After the test, functions shall be self-recoverable and the equipment shall operate as intended and the equipment shall have no loss of critical stored data.

Performance criteria for ETSI EN 301 489-52 V1.2.1 (2021-11)

1) Performance criteria for Continuous phenomena applied to Transmitters (CT)

With a link established, during the test, the uplink speech output level shall be at least 35 dB less than the previously recorded reference levels, when measured through an audio band pass filter of width 200 Hz, centred on 1 kHz (audio breakthrough check).

NOTE: When there is a high-level background noise present, the filter bandwidth may be reduced down to a minimum of 40 Hz.

In idle mode, the transmitter shall not operate unintentionally.

At the conclusion of the test, the EUT shall operate as intended with no loss of user control functions or critical stored data, and the communication link shall have been maintained.

2) Performance criteria for Continuous phenomena applied to Receivers (CR)

During the test, the RXQUAL of the downlink shall not exceed the value of three, measured during each individual exposure in the test sequence.

In the case of narrow band responses, the procedure in clause 4.4.1 shall be followed.

During the test, the downlink speech output level shall be at least 35 dB less than the previously recorded reference levels, when measured through an audio band pass filter of width 200 Hz, centred on 1 kHz (audio breakthrough check).

NOTE: When there is a high-level background noise present, the filter bandwidth may be reduced down to a minimum of 40 Hz.

At the conclusion of the test, the EUT shall operate as intended with no loss of user control functions or critical stored data, and the communication link shall have been maintained.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5. LIST OF MEASURING EQUIPMENT

LINE CONDUCTED EMISSION

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|-------------------------------------|--------------|-----------|------------|------------|------------|
| 1 | EMI Test Software | Farad | EZ | / | N/A | N/A |
| 2 | EMI Test Receiver | R&S | ESR3 | 102312 | 2023-02-15 | 2024-02-14 |
| 3 | Artificial Mains | R&S | ENV216 | 101288 | 2022-06-16 | 2023-06-15 |
| 4 | Pulse Limiter | R&S | ESH3-Z2 | 102750-NB | 2022-08-19 | 2023-08-18 |
| 5 | Impedance Stabilization Network | TESEQ | ISN T800 | 45130 | 2022-10-29 | 2023-10-28 |
| 6 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

RADIATED DISTURBANCE

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|-------------------------------------|--------------|------------|-------------|------------|------------|
| 1 | EMI Test Software | Farad | EZ | / | N/A | N/A |
| 2 | 3m Full Anechoic Chamber | MRDIANZI | FAC-3M | MR009 | 2021-09-25 | 2024-09-24 |
| 3 | Positioning Controller | Max-Full | MF7802BS | MF780208586 | N/A | N/A |
| 4 | By-log Antenna | SCHWARZBECK | VULB9163 | 9163-470 | 2021-09-12 | 2024-09-11 |
| 5 | Horn Antenna | SCHWARZBECK | BBHA 9120D | 9120D-1925 | 2021-09-05 | 2024-09-04 |
| 6 | EMI Test Receiver | R&S | ESPI | 101940 | 2022-08-18 | 2023-08-17 |
| 7 | Broadband Preamplifier | / | BP-01M18G | P190501 | 2022-06-16 | 2023-06-15 |
| 8 | MXA Signal Analyzer | Agilent | N9020A | MY50510140 | 2022-10-29 | 2023-10-28 |
| 9 | RS SPECTRUM ANALYZER | R&S | FSP40 | 100503 | 2022-10-29 | 2023-10-28 |
| 10 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

VOLTAGE FLUCTUATION AND FLICKER/HARMONIC CURRENT EMISSIONS

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--|--------------|-----------|------------------|------------|------------|
| 1 | HARMONICS&FLICKER MEASUREMENT SYSTEM | EVERFINE | HFM-3000 | P630850CD1411116 | 2023-02-07 | 2024-02-06 |
| 2 | HARMONICS&FLICKER TESTING POWER SOURCE | EVERFINE | HFS-4000 | P624486CD1411124 | 2023-02-07 | 2024-02-06 |
| 3 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

RF ELECTROMAGNETIC FIELD

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--|--------------|----------------|-------------------|------------|------------|
| 1 | RS Test Software | Tonscend | / | / | N/A | N/A |
| 2 | MXG Vector Signal Generator | Agilent | E4438C | MY42081396(6 G) | 2022-06-16 | 2023-06-15 |
| 3 | 3m Full Anechoic Chamber | MRDIANZI | FAC-3M | MR009 | 2021-09-25 | 2024-09-24 |
| 4 | RF POWER AMPLIFIER | OPHIR | 5225R | 1052 | 2022-06-16 | 2023-06-15 |
| 5 | RF POWER AMPLIFIER | OPHIR | 5273F | 1019 | 2022-06-16 | 2023-06-15 |
| 6 | RF POWER AMPLIFIER | SKET | HAP_0306G -50W | / | 2022-06-16 | 2023-06-15 |
| 7 | Stacked Broadband Log Periodic Antenna | SCHWARZBECK | STLP 9128 | 9128ES-145 | NCR | NCR |
| 8 | Stacked Mikrowellen Log.-Per Antenna | SCHWARZBECK | STLP 9149 | 9149-482 | NCR | NCR |
| 9 | RS Electric field probe | narda | EP 601 | 611WX80208 | 2022-06-16 | 2023-06-15 |
| 10 | Sound Level meter | BK Precision | 735 | 7350087310010 020 | 2022-06-16 | 2023-06-15 |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--|---------------|--------------------|----------------------------|------------|------------|
| 11 | Audio Analyzer | R&S | UPV | 1146.2003K02-1 01721-UW | 2022-10-29 | 2023-10-28 |
| 12 | Mouse Simulation | Bruel & Kjaer | 4227 | A0304216 | 2022-06-16 | 2023-06-15 |
| 13 | Ear Simulation and supply | Bruel & Kjaer | 2669.4182.5 935 | A0305284 | 2022-06-16 | 2023-06-15 |
| 14 | Acoustical Calibrators | Bruel & Kjaer | 4231 | A0304215 | 2022-06-16 | 2023-06-15 |
| 15 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

Note: NCR means no calibration requirement

ELECTROSTATIC DISCHARGE

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--|--------------|-----------|------------|------------|------------|
| 1 | ESD Simulator | SCHLODER | SESD 230 | 604035 | 2022-07-18 | 2023-07-17 |
| 2 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

ELECTRICAL FAST TRANSIENT IMMUNITY

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--|--------------|-----------|------------|------------|------------|
| 1 | Immunity Simulative Generator | EM TEST | UCS500-M4 | 0101-34 | 2022-08-17 | 2023-08-16 |
| 2 | Electric fast pulse group generator | 3ctest | EFT-4001G | EC0461044 | 2022-10-31 | 2023-10-30 |
| 3 | Capacitive coupling clamp | 3CTEST | EFTC | EC0441098 | 2022-06-16 | 2023-06-15 |
| 4 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

RF COMMON MODE

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|---|--------------|-----------|------------|------------|------------|
| 1 | Simulator | FRANKONIA | CIT-10/75 | A126A1195 | 2022-08-17 | 2023-08-16 |
| 2 | CDN | FRANKONIA | CDN-M2+M3 | A2210177 | 2022-06-16 | 2023-06-15 |
| 3 | 6dB Attenuator | FRANKONIA | DAM25W | 1172040 | 2022-06-16 | 2023-06-15 |
| 4 | Electromagnetic coupling injection clamp | ZHINAN | ZN23203 | 14017 | 2022-06-16 | 2023-06-15 |
| 5 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

SURGES, LINE TO LINE AND LINE TO GROUND

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|---|--------------|-----------|------------|------------|------------|
| 1 | Immunity Simulative Generator | EM TEST | UCS500-M4 | 0101-34 | 2022-08-17 | 2023-08-16 |
| 2 | Communication wave lightning generator | HTEC | HTSG 70 | 181701 | 2022-10-31 | 2023-10-30 |
| 3 | Symmetrical data line coupling network | HTEC | HCN 8 | 182701 | 2022-10-31 | 2023-10-30 |
| 4 | Data line decoupling network | HTEC | HDEC 8 | 182702 | 2022-10-31 | 2023-10-30 |
| 5 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |

VOLTAGE DIPS/INTERRUPTIONS IMMUNITY TEST

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--|--------------|-----------|------------|------------|------------|
| 1 | Voltage dips and up generator | 3CTEST | VDG-1105G | EC0171014 | 2022-06-16 | 2023-06-15 |
| 2 | WIDEBAND RADIO COMMUNICATION TESTER | R&S | CMW 500 | 103818 | 2022-06-16 | 2023-06-15 |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



6. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix B for Photographs of Test Setup_EMC

7. PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix C for Photographs of The EUT.

-----THE END OF REPORT-----

